

ReNew Rubber Flooring Highlights

ReNew Rubber is a tough and durable flooring option that brings easy maintenance and wear resistance to any project. While typically thought of for gym and fitness applications, ReNew™ Rubber's colorful combinations allow for a variety of uses in any application.

SBR and EPDM Rubber:

- SBR (synthetic butyl rubber) is recycled rubber – Our SBR is sourced exclusively from commercial grade truck tires, meaning it is superior quality to those coming from all tire forms. This SBR is 100% post-consumer recycled material.
- EPDM is the colored granules – sourced exclusively for low odor, and high UV resistance, for clearer and more long-lasting color
- ReNew Rubber comes in 100% recycled (all black), and the recycled content is reduced proportionally to the amount of color added.

General Benefits:

- Roll goods allow for fewer seams compared to tile
- Rubber is unique amongst other floors – it gets less slippery when wet. This means it is ideal for any area where water and potential falling hazards may occur
- ReNew Rubber has a high “bounce back” property in that it will retain its form despite wear
- Extremely durable and easy to clean. ReNew Rubber also does not require a sealant upon installation, allowing for easy install and no wear layer to scuff or re-apply.
- Great comfort under foot, reduced impact and outstanding acoustical properties

General Notes:

- 4mm is suitable for most standard applications, including most fitness areas. 9mm is necessary for larger free weights and for increased impact absorption.
- Made in the USA
- Green Circle Certified for sustainable manufacturing and recycled content.
- Installed in Ice Rinks, Stadiums, Ski-Resorts, Fitness Areas – anywhere needing the safety, durability and resilience of Siena Rubber.
- ReNew Rubber Interlocking tile can be loose-laid over almost any sub-floor or finished floor, without permanent bonding to the substrate. ReNew stays in place until you're ready to remove it or relay it.



Formats:

- 4mm | 8mm | 9mm Tile & Rolls
(depending on color)
- Tiles: 23" x 23"
(straight edge or interlock – depending on color)
- Rolls: 48" x 25' | 48" x 50'
- *4mm Tile*: Straight edge only
- *8mm & 9mm Tile*: Straight edge or interlocking – depending on color

Specifications:

- Density: ASTM D3676 60 pcf
- Hardness: ASTM D2240 (Shore A) 65 +/- 5
- Tear Strength: ASTM D624 80 pli min
- Elongation: ASTM D412 > 145%
- Tensile Strength: ASTM D412 > 220 PSI
- Flexibility: ASTM F137 1/4" Mandrel Pass
- Resistance to Chemicals: ASTM F925 No Change
- LEED Qualification: Qualifies for Material and Resources Credit

01.2025

allstaterubber.com

Allstate Rubber 2220 S Hamilton Extension
Dalton, Georgia 30720